

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** Wall Light

**Supplier's address:** Zhongshan Zhaoliang Lighting Co., Ltd., 7/F, No. 30 Qingji Street, Tiebian Village, Henglan Town, Zhongshan City, China

**Model identifier:** 30786501

## Type of light source:

|                                                     |                    |                                 |      |
|-----------------------------------------------------|--------------------|---------------------------------|------|
| Lighting technology used:                           | LED                | Non-directional or directional: | NDLS |
| Light source cap-type (or other electric interface) | Connection by wire |                                 |      |
| Mains or non-mains:                                 | MLS                | Connected light source (CLS):   | No   |
| Colour-tuneable light source:                       | No                 | Envelope:                       | -    |
| High luminance light source:                        | No                 |                                 |      |
| Anti-glare shield:                                  | No                 | Dimmable:                       | No   |

## Product parameters

| Parameter | Value | Parameter | Value |
|-----------|-------|-----------|-------|
|-----------|-------|-----------|-------|


### General product parameters:

|                                                                                                                                                       |        |                      |                                                                                                                                                            |                        |
|-------------------------------------------------------------------------------------------------------------------------------------------------------|--------|----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------|
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer                                                                         |        | 6                    | Energy efficiency class                                                                                                                                    | E                      |
| Useful luminous flux ( $\phi_{\text{use}}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) |        | 675 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 3 000                  |
| On-mode power ( $P_{\text{on}}$ ), expressed in W                                                                                                     |        | 6,0                  | Standby power ( $P_{\text{sb}}$ ), expressed in W and rounded to the second decimal                                                                        | 0,00                   |
| Networked standby power ( $P_{\text{net}}$ ) for CLS, expressed in W and rounded to the second decimal                                                |        | -                    | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set                                                         | 80                     |
| Outer dimensions without separate control gear, light-                                                                                                | Height | 235                  | Spectral power distribution in the range 250 nm to 800 nm, at full-load                                                                                    | See image in last page |
|                                                                                                                                                       | Width  | 235                  |                                                                                                                                                            |                        |
|                                                                                                                                                       | Depth  | 60                   |                                                                                                                                                            |                        |

|                                                                                                                         |      |                                       |                |  |
|-------------------------------------------------------------------------------------------------------------------------|------|---------------------------------------|----------------|--|
| ing control parts and non-lighting control parts, if any (millimetre)                                                   |      |                                       |                |  |
| Claim of equivalent power <sup>(a)</sup>                                                                                | -    | If yes, equivalent power (W)          | -              |  |
|                                                                                                                         |      | Chromaticity coordinates (x and y)    | 0,313<br>0,337 |  |
| <b>Parameters for LED and OLED light sources:</b>                                                                       |      |                                       |                |  |
| R9 colour rendering index value                                                                                         | 1    | Survival factor                       | 0,90           |  |
| the lumen maintenance factor                                                                                            | 0,96 |                                       |                |  |
| <b>Parameters for LED and OLED mains light sources:</b>                                                                 |      |                                       |                |  |
| displacement factor (cos $\phi_1$ )                                                                                     | 0,70 | Colour consistency in McAdam ellipses | 5              |  |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. | -(b) | If yes then replacement claim (W)     | -              |  |
| Flicker metric (Pst LM)                                                                                                 | 0,9  | Stroboscopic effect metric (SVM)      | 0,8            |  |

(a) '-': not applicable;

(b) '-': not applicable;



Model placed on the Union market from 07/01/2024



**EPREL registration number:** 1902646

<https://eprel.ec.europa.eu/qr/1902646>

**Supplier:** StoneX Trading (Authorised representative)

**Website:** <https://goecolighting.fr/>

**Customer care service:**

**Name:** Zhongshan Zhaoliang Lighting Co., Ltd.

**Website:**

**Email:** [goecolightingfr@163.com](mailto:goecolightingfr@163.com)

**Phone:** +447845991423

**Address:**

7/F, No. 30 Qingji Street, Tiebian Village, Henglan Town, Zhongshan  
City, China